

Highlights:

- In depth adjustable
- Stores up to 3 units of 19" Equipment
- Punched square holes for use with snap-in cage nuts
- Loading capacity of 100 Kg
- 2.5 mm thick cold rolled steel frame
- Easy assembly in 10 minutes
- Floor standing & wall mounted use
- Unrestricted air flow due to open-frame design
- Stand alone & in-furniture integration
- Ships as flat-down package

The OPR303A is an in depth adjustable professional and solid constructed open-frame rack for 19" equipment compliant to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards which is suitable for wall mounted or floor standing installation. It ensures maximum installation, connectivity and maintenance ease storing up to 3 units of 19" equipment.


The open-frame rack has an adjustable depth of 300 to 450 mm for easy installation and fitment in existing furniture. The rugged construction made of 2 mm thick steel allows pre-loading of the equipment before transportation to the installation site. Finishing is done in a black (RAL9004) powder coating with fine structure while punched equipment mounting profiles on front and both sides offer a multifunctional use of the cabinet. Delivered in a flat-down package, the simple structure allows assembly by a single person in a record-breaking time.



Product Features:

Unit height	3 HE	
Max. usable depth	300 ~ 450 mm	
Max. load standing	100 kg	
Max. load hanging	50 kg	
Dimensions	520 x 158 x 300~450 mm (W x H x D) (excl. rubber feet)	
Colours	Black (RAL9004)	
Accessories	Included	4 x Leveling feet
		4 x M8 expanding wall bolt
		24 x Cage nuts + screws

Technical drawings:



OPR303A

Product description:
19" OPEN FRAME RACK - 3 UNIT - 300-450MM

Weight:

TBA

Outer dimensions:
(w x h x d)

527 x 187,9 x 450

Unit height:

3 HE