


Highlights:

- In depth adjustable
- Stores up to 6 units of 19" Equipment
- Punched square holes for use with snap-in cage nuts
- 2 mm thick cold rolled steel frame
- Easy assembly in 10 minutes
- Floor standing & wall mounted use
- Unrestricted air flow due to open-frame design
- Stand alone & in-furniture integration
- Ships as flat-down package



The OPR506A is an in depth adjustable professional and solid constructed open frame rack for 19" equipment compliant to ANSI/EIA RS-310D, DIN41491 and IEC60297 standards which is suitable for wall mounted or floor standing installation. It ensures maximum installation, connectivity and maintenance ease storing up to 6 units of 19" equipment.

The open frame rack has an adjustable depth of 500 to 800 mm for easy installation and fitment in existing furniture. The rugged construction made of 2 mm thick steel allows pre-loading of the equipment before transportation to the installation site. Finishing is done in a black (RAL9004) powder coating with fine structure while punched equipment mounting profiles on front and both sides offer a multifunctional use of the cabinet. Delivered in a flat-down package, the simple structure allows assembly by a single person in a record-breaking time.

Product Features:

Unit height	6 HE
Max. usable depth	500 ~ 800 mm
Dimensions	520 x 291 x 500~800 mm (W x H x D) (excl. rubber feet)
Colours	Black (RAL9004)
Accessories	Included 4 x Levelling feet 4 x M8 expanding wall bolt 12 x Cage nuts + screws