

# EclMiniFresnel VW

60W Variable White LED Mini Fresnel (2,700K - 5,600K), with manual zoom 21° - 83°

ORDER CODE: MINIECLFRVW



The **EclMiniFresnel VW** is an ultra-compact LED Fresnel lamp, designed as a replacement for a 300W fixture, with a bright and high-quality variable-white light, from 2,700K to 5,600K, using a 60W LED source. This is the perfect luminaire for those applications requiring high-quality white rendering, such as in TV studios, galleries, and virtual productions, with high CRI (>96), TLCI (>96), TM-30 and R9. The **EclMiniFresnel VW** has a manual zoom range from 21° to 83°, with precise focusing, and barndoors (included). This fixture has an intuitive user interface with rotatory knobs. It also has stand-alone settings, PowerCon True in & through connections and XLR in & through, offering an incredible user experience and easy setup.

## MAIN FEATURES

- Linear white CCT, from 2,700K to 5,600K
- 60W Variable White LED with CRI >96; TLCI >96; high TM-30 and R9
- Barndoors and filter frame included

## VERSIONS

Code	Housing
MINIECLFRVWBK	Black
MINIECLFRVWWH	White

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 60W Variable White LED
- CCT: 2,700 K - 5,600
- Luminous flux: (21°) 877 lm - (83°) 2'320 lm @full
- Lux: (21°) 630 lx - (83°) 238 lx @3 m
- CRI: 96 @WW; 95 @CW; 95 @full
- R9: 91 @WW; 88 @CW; 86 @full
- TLCI: 95 @WW; 98 @CW; 97 @full
- TM30 Rf: > 94 @WW; > 93 @CW; > 94 @full
- TM30 Rg: < 103 @WW; < 104 @CW; < 104 @full
- Source life expectancy: > 50.000 h

### OPTICS

- Zoom: 21° - 83 ° manual
- Lens diameter: 3,93" - 100 mm
- Lens type: fresnel zoom lens

### COLOUR SYSTEM

- Colour mixing: tunable white
- CCT: CCT control through dedicated DMX channel
- White presets: 2,700 K - 5,600 K
- Colour wheel: built-in white presets

### DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer
- Static mode: selection of static dimmer and color temperature
- Manual mode: manual adjustment of intensity and CT from knob
- Auto mode: built-in programs with execution speed adjustment

### BODY

- Hardware on-board: filter frame, 4 doors barndoors, spigot
- Body: sturdy die-cast aluminium body
- Body colour: RAL 9004 or RAL 9003


## ACCESSORIES & RELATED PRODUCTS

▪ C6002B	Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
▪ C6040B	Aluminum clamp for 28mm spigot, 200kg load, 48-51mm tubes, black
▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
▪ TOUR53415L03	Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m



▪ ECLFRSPG	Spigot for PROLIGHTS fixtures
▪ MINIECLFRBD	Black barn door 4 directional flaps to adjust the light beam
▪ MINIECLFRTPG	Filter frame for MINIECLFR series
▪ SPGM10	28mm spigot for fixtures, M10 bolt
▪ SPGM12	28mm spigot for fixtures, M12 bolt
▪ UPBOX1U	Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT

**PRESET FULL ON**

Beam angle 50%: 20°


**PRESET FULL ON**

Beam angle 50%: 65°


**TECHNICAL DRAWINGS**

**CERTIFICATIONS / APPROVALS**
