

## Highlights:

- Stores up to 18 units of 19" Equipment
- Standard keylock for both doors
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Tempered glass door with keylock
- front and rear in depth adjustable 19" profiles (max 540 mm)
- Reversible door position



The SPR618 is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provides a solid and stable construction making it suitable for heavy equipment, storing up to 18 units inside. The SPR618 comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and leveling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19" profiles provide great flexibility for installing equipment depending on its depth. Both front and rear doors are fitted with a standard keylock.

## Product Features:

Dimensions	600 x 918 (988) x 600 mm (W x H (incl. feet) x D)	
Unit height	18 HE	
Max. usable depth	540 mm	
Wheel	Diameter	50 mm
Colours	Black (RAL9004)	
Weight	52 kg	