



# HS208TMK2

Full range horn speaker 8" 100V

## Highlights:

- Barrier terminal block in waterproof connection box
- Multi-Layer glass composite material with textured EPDM black coating
- IP65 Ingress protection
- Multi-tapping 100V line transformer
- 8" high output woofer with a 1.3" voice coil


The AUDAC HS208TMK2 is a full-range loudspeaker system engineered to provide long throw, full range sound projection in a variety of fixed in- and outdoor applications. Its wide, smooth frequency response and high efficiency ensure high-fidelity music reproduction along with superb projection of clear, intelligible speech at very low distortion. The HS208TMK2 features a 1,3" HF driver with an 8" LF loudspeaker combination for the best sound reproduction, and has a very special coverage pattern of 40° horizontally and vertically. The HS208TMK2 contains the possibility to choose from power tapping for: - 120 Watt, 60 Watt, 30 Watt @ 100V - 8 Ohm impedance. The construction of the HS208TMK2 is made of polyester with textured EDPM black coating and a perforated aluminum grill front finish. Behind the aluminum grill, there is an acoustic foam assembled, which prevents rain coming into the speaker. Due to an Ingress Protection rating (IP) of 65, this speaker is suitable for any environment where humidity or moisture are present. At the rear, you will find cable clamps to select the line transformator as desired. The cable clamps are shielded to obstruct moisture and humidity Mounting bracket: - MBK208Z



## Certification:



## Voltage:



## Applications:

- Sport facilities
- Events
- Corporate spaces

## System specifications:

---

Speaker type	2-way horn speaker	
Max. Power	300 W	
RMS Power	150 W	
Impedance	8 Ω	
Line Transformer Tappings	1	120 W / 83 Ω
	2	60 W / 167 Ω
	3	30 W / 333 Ω
Sensitivity (1W/1m)	97 dB	
Sound Pressure (Max. W/1m)	123 dB	
Frequency	Response (± 3 dB)	100 Hz - 18 kHz
	Range (-10 dB)	70 Hz - 20 kHz
Crossover	Frequency	1.5 kHz
	Type	Passive built-in
Dispersion	Horizontal	40°
	Vertical	40°
Ingress Protection rating	IP65	
Connectors	Barrier terminal block in waterproof connection box	
Drivers	HF	1.3" Compression driver
	MF	8"

## Product Features:

---

Dimensions	360 x 360 x 482 mm (W x H x D)
Weight	15.600 kg
Construction	Multi-Layer glass composite material with textured EPDM black coating
Front finish	Powdercoated aluminium with lining
Mounting & handling	Mounting bracket fixing holes
Colours	Black (RAL9005)